

digitalTM MATERIAL SAFETY DATA SHEET

MAINTENANCE CARTRIDGE

Page 1 of 2

A-SP-ELMD019-AA-0 Rev A.

SECTION 1 - PREPARATION/PRODUCT INFORMATION

Manufacturer's Name: Digital Equipment Corporation Maynard, MA USA

Non-Emergency Phone Number: (508) 496-9242

Emergency Phone Numbers: 800-228-5635 ext.123
[+1] 612-221-3999 ext.123

Preparation Date: March 4, 1992

Supersedes: April 2, 1990

Product Name: Maintenance Cartridge

Part Number(s): LCGX1-JW

Use: Equipment Maintenance

SECTION 2 - INGREDIENTS

HAZARDOUS INGREDIENTS	CAS	%	ACGIH TLV	OSHA PEL	CARCINOGEN LIST			SARA 313
					IARC	NTP	OSHA	

None Maintenance Cartridge is classified as an article. Maintenance Cartridge contains ethylene glycol. See Section 8 for safe handling/preventive measures.

All ingredients contained in this product are on the US TSCA inventory.

SECTION 3 - PHYSICAL AND CHEMICAL DATA

Boiling Point - Not applicable
Vapor Pressure - Not applicable
Vapor Density - Not applicable
Appearance - Fluid in cartridge
Freezing Point - Not applicable
Melting/Softening Point - Not available

Solubility in Water - < 0.1%
Percent Volatile - None
Evaporation Rate - Not applicable
Odor and Odor Threshold - None
pH - Not applicable
Specific Gravity - Not applicable

SECTION 4 - FIRE AND EXPLOSION HAZARD

Flash Point - None
Auto-Ignition Temperature - 775°C (1427°F)
Unusual Fire or Explosion Hazards - None
Hazardous Combustion Products - Carbon monoxide, carbon dioxide

Special Fire Fighting Procedure - None
Flammable Limits - None
Extinguishing Media - Water, foam, carbon dioxide

SECTION 5 - REACTIVITY DATA

Stability - Stable

Conditions to Avoid - None

Incompatibility - None

Hazardous Polymerization -None

Hazardous Decomposition Products - Not available

SECTION 6 - HEALTH HAZARD DATA/TOXICOLOGICAL PROPERTIES

Hazard to Humans- None during normal use. Exposure to the fluid could occur during handling. Accidental exposure to fluid containing ethylene glycol could result in lung irritation, dizziness, nausea and kidney damage.

Animal Experiment- None

Additional Information- See Section 8 for safe handling/preventive measures. Fluid contains non-hazardous ingredients and ethylene glycol which is listed on SARA, OSHA and ACGIH list of hazardous chemicals. The OSHA PEL for ethylene glycol is 50 ppm.

SECTION 7 - EMERGENCY/FIRST AID PROCEDURE

(Applies to fluid in cartridge)

If Inhaled - Remove to fresh air. Support breathing if necessary and contact a physician.

If on Skin - Promptly wash skin with soap and water.

If in Eyes - Flush eyes with large quantities of water for at least 15 minutes.

If Swallowed- Seek immediate medical attention.

SECTION 8 - SAFE HANDLING/PREVENTIVE MEASURES

Personal Protective Equipment - None for normal use.

Engineer Control - Not needed.

Waste Disposal - No special requirements.

Procedures for Leaks or Spills- Wipe up fluid with absorbent material.

Work Practices - None

Storage Requirement- Keep container closed.

Handling Procedure/Equipment- Place an absorbent towel in front of the cartridge slot to catch any fluid as the cartridge is removed.

Labelling- None

WHMIS Classification- Not applicable

SECTION 9 - TRANSPORTATION REQUIREMENTS

None